

■ 要目表

口径 mm	機 名	出力 kW	吐出し量 m ³ /min	全揚程 m	吐出し量 m ³ /min	全揚程 m	標準許容 押込圧力 MPa{kgf/cm ² }	防振架台適用表	
								DAS型	DB型
32×32	32×32FSFDN6.25A	0.25	0.040	11.5	0.150	5.0	0.56{5.7}	DAS-10	DB-1
	32×32FSFDN6.4A	0.4	0.040	16.5	0.150	8.5	0.50{5.0}	DAS-10	DB-1
	32×32FSFDN6.75A	0.75	0.040	24.0	0.150	15.0	0.43{4.3}	DAS-10	DB-1
	32×32FSFDN61.5A	1.5	0.040	36.0	0.150	28.0	0.31{3.1}	DAS-10	DB-1
	32×32FSGDN62.2A	2.2	0.040	48.0	0.150	41.0	0.51{5.2}	DAS-10	DB-1
	32×32FSGDN63.7A	3.7	0.040	64.0	0.150	58.0	0.35{3.5}	DAS-1	DB-1
40×32	40×32FSEDN6.4A	0.4	0.090	11.3	0.230	5.0	0.87{8.8}	DAS-10	DB-1
	40×32FSEDN6.75A	0.75	0.090	18.0	0.270	9.1	0.80{8.1}	DAS-10	DB-1
	40×32FSFDN61.5A	1.5	0.090	29.0	0.270	18.0	0.68{6.9}	DAS-10	DB-1
	40×32FSGDN62.2A	2.2	0.090	39.0	0.275	23.5	0.59{6.0}	DAS-10	DB-1
	40×32FSGDN63.7A	3.7	0.090	56.0	0.275	44.5	0.42{4.2}	DAS-1	DB-1
	40×32FSGDN65.5A	5.5	0.090	66.0	0.275	56.0	0.32{3.2}	DAS-1	DB-1
50×40	50×40FSEDN6.75A	0.75	0.125	13.0	0.375	7.0	0.84{8.5}	DAS-10	DB-1
	50×40FSEDN61.5A	1.5	0.125	23.4	0.375	14.0	0.75{7.6}	DAS-10	DB-1
	50×40FSFDN62.2A	2.2	0.125	30.8	0.375	20.0	0.67{6.8}	DAS-10	DB-1
	50×40FSGDN63.7A	3.7	0.125	48.0	0.375	32.0	0.51{5.2}	DAS-1	DB-1
	50×40FSGDN65.5A	5.5	0.125	61.0	0.375	48.0	0.38{3.8}	DAS-1	DB-1
	50×40FSHDN67.5A	7.5	0.090	75.6	0.375	59.0	0.23{2.3}	DAS-2	DB-1
65×50	65×50FSEDN61.5A	1.5	0.250	16.2	0.700	7.7	0.82{8.3}	DAS-10	DB-1
	65×50FSEDN62.2A	2.2	0.250	20.3	0.750	11.5	0.77{7.8}	DAS-10	DB-1
	65×50FSFDN63.7A	3.7	0.250	31.5	0.700	18.5	0.66{6.7}	DAS-1	DB-1
	65×50FSGDN65.5A	5.5	0.250	43.0	0.750	25.0	0.55{5.6}	DAS-1	DB-1
	65×50FSHDN67.5A	7.5	0.250	53.0	0.750	31.5	0.44{4.4}	DAS-2	DB-2
	65×50FSHDN611A	11	0.250	70.3	0.750	48.5	0.27{2.7}	DAS-2	DB-2
80×65	80×65FSEDN63.7A	3.7	0.500	20.5	1.300	11.5	0.77{7.8}	DAS-1	DB-1
	80×65FSFDN65.5A	5.5	0.500	29.2	1.500	13.2	0.68{6.9}	DAS-1	DB-1
	80×65FSFDN67.5A	7.5	0.500	35.0	1.500	20.0	0.62{6.3}	DAS-2	DB-1
	80×65FSGDN611A	11	0.500	49.8	1.500	28.0	0.48{4.8}	DAS-2	DB-2